



INSTALLATION INSTRUCTIONS CHEVROLET MALIBU (1997-2000)

PART NUMBER: CV-52-97

VIEW INSTRUCTIONS & UPDATES
ONLINE @
WWW.PRO-FIT-INTL.COM

PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS Pro.Fit VSM™.
All instructions assume a drivers seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

Pro.Fit logo and part number will be right side up and readable when installed.

TOOLS REQUIRED: Hook tool, 9/32" socket and driver.

PARTS INCLUDED: Pro.Fit VSM™, instructions.

LOCATION: To the right of the radio.

STEP 1.

Begin by inserting hook tool under cover for ignition switch and pulling back to release two (2) clips Set cover aside. Starting by ignition switch, insert hook tool behind trim bezel which surrounds the climate control and radio and pull toward you to release two (2) clips. Continue working bezel loose with hands until removed. Do not disconnect wiring. Let bezel hang.



STEP 2.

With 9/32" socket and driver locate and remove the factory screw to right of the radio. Align Pro.Fit VSM™ over screw hole and centering pin. Insert factory screw and tighten.



STEP 3.

Install trim bezel back into position. Put ignition cover back into position. Attach hang-up cup onto Pro.Fit VSM™.

This completes the installation of your Pro.Fit VSM™.



Pro.Fit International, Inc.® may not be held liable for any damage to a vehicle before, during or after the installation or removal of this Pro.Fit VSM™. Pro.Fit may not be held liable for any personal injury resulting from accident or improper installation.

Pro.Fit International, Inc.® 1335 Eagandale Court, Eagan, MN 55121, Ph: 651-688-3588 or 800-388-0073 Fx: 651-688-9876

Web Address: www.pro-fit-intl.com

© Pro.Fit International, Eagan, MN 2003