



## Chrysler Town & Country 2008-2010 Dodge Caravan 2008-2010 (With and without NAV)



### DG-92-08-G3

#### PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS VSM G3

All instructions assume a drivers seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

**TOOLS REQUIRED:** Dash Trim Removal Tool (DTRT), Hook Tool Set (DM-30-22), Phillips screw driver

**PARTS INCLUDED:** VSM G3, A Plate, J Stem

**LOCATION:** Right of Radio

**STEP 1.** The dash molding forms a slight overhang above the radio. Underneath this overhang are two rectangular plastic covers. Use the pointed end of the hook tool to gently remove these two plastic covers by gently pulling downwards on the sides of the covers with the hook tool. Removing these plastic covers reveals two Phillips screws which must be removed next. Set the plastic covers and the two Phillips screws aside.



**STEP 2.** Gently lift up on the overhang to release a series of retainer clips. Lifting up on this overhang will reveal two more Phillips screws directly above the radio. Remove these two screws as well. Place the DTRT behind the radio bezel in the exact location that you just removed the two Phillips screws. Work the DTRT around the radio bezel releasing retainer clips.



**STEP 3.** Place the VSM G3 flush and to the right of the radio exactly in place as pictured in Photo #3. Replace the Phillips screw over the pilot hole in the leg of the VSM G3 and tighten the VSM G3 evenly and securely in place as pictured.



**STEP 4.** After the VSM G3 is flush and tightened, begin to assemble the dash back in the reverse order in which it was disassembled. You have successfully installed your VSM G3.



Note: Note: See the Assembly Instructions for G3 Components for additional information.

Pro.Fit International, Inc.® may not be held liable for any damage to a vehicle before, during or after the installation or removal of this VSM G3™. Pro.Fit International may not be held liable for any personal injury resulting from accident or improper installation. Pro.Fit International, Inc.® 1335 Eagandale Court, Eagan, MN 55121, Ph: 651.688.3588 or 800.388.0073 Fx: 651.688.9876

Installation Difficulty  
● ○ ○ ○ ○  
Simple Advanced

© Pro.Fit International, Eagan, MN 2008

View Instruction & Updates  
Online at  
[www.pro-fit-intl.com](http://www.pro-fit-intl.com)