



## LOBOY Mount LB-600

### IMPORTANT NOTICE

A Surface Preparation Cleaning Kit and Alcohol Pad have been included to clean the mounting location prior to installing the LoBoy. Failure to properly prepare the mounting surface may result in the Flex Pad failing to adhere and voiding the warranty. Do not apply to leather surfaces. Do not adjust the torque setting on the LoBoy's center screw

**PARTS INCLUDED:** LOBOY Mount, instructions, surface prep kit, L-Bracket (LB-650), hardware pack  
**NOTE:** (Holder or cradle not included.)

**STEP 1.** Select a preferred mounting location and configure with or without the "L bracket". (The L bracket may not be required for your application.) Attach a holder or cradle(not included) and experiment with mounting positions. Try to avoid blocking any controls or amenities in your vehicle.

**STEP 2.** Clean the mounting location using the Surface Preparation Cleaning Kit. To assure maximum Flex Pad adhesion, clean the mounting location according to the directions on the back of the Cleaning Kit. **Failure to properly prepare the mounting surface may result in the Flex Pad failing to adhere and voiding the warranty.** After cleaning with the Surface Prep Kit, clean the mounting location with the alcohol swab and allow to dry.

**STEP 3.** Peel the tape liner off the Flex Pad, press onto the mounting location and apply firm pressure for a minimum of 30 seconds, pressing down all around the flex pad. **3M recommends that the adhesive "cure" for 72 hours before using.**

**STEP 4.** Attach your electronic device to the LoBoy using one of the following methods. The LoBoy may be swiveled to make the final installation easier.

**Manufacturer's hardware** - Insert bolts through the back of the LoBoy and into the back of the device. Tighten bolts.

**Included hardware** - Hold a nut on the backside of the LoBoy, insert a bolt through front of car kit or mounting plate and tighten. Install all four (4) bolts in this manner.



Pro.Fit International, Inc.® may not be held liable for any damage to a vehicle before, during or after the installation or removal of this Pro.Fit VSM®. Pro.Fit may not be held liable for any personal injury resulting from accident or improper installation. Pro.Fit International, Inc.® 1335 Eagandale Court, Eagan, MN 55121, Ph: 651-688-3588 or 800-388-0073 Fx: 651-688-9876

Installation Difficulty  
 ● ○ ○ ○ ○  
 Simple Advanced

© Pro.Fit International, Eagan, MN 2006

VIEW INSTRUCTIONS & UPDATES  
 ONLINE @  
 WWW.PRO-FIT-INTL.COM