



Ford Explorer 2011-2012

Part Number: MV-25-03-G3



PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS VSM G3
All instructions assume a drivers seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

**When properly installed, the metal between the ball and 2 small holes is all that is exposed.
(Some exceptions apply).**

TOOLS REQUIRED: DTRT (Dash Trim Removal Tool), 7mm Socket and Driver, 5/64" bit and drill, Phillips screwdriver, marking pen

PARTS INCLUDED: VSM-G3, Lock-Plate, J-Stem, two (3) #8 x 1/2" screws

LOCATION: Right of Radio

1. Use the DTRT (Dash Trim Removal Tool) to remove the trim bezels on each side of the radio/climate control (picture 1). Begin towards the bottom portion of these trim bezels and release a series of retainer clips. A push pin secures the upper portion of this bezel piece and requires significant effort to release. Be cautions not use to much force in releasing the push pin. Once you have removed each trim piece, simply set them carefully aside.
2. The removal of the these trim pieces will reveal four (4) 7mm bolts that secure the bezel that contains the climate control/display/air vents. Carefully remove these bolts and again use the DTRT around this bezel. Do not disconnect the wiring to this bezel, simply allow to hang out of the way.
3. Place the **VSM-G3** in place against the inner dash molding as pictured (picture 2). Use the **VSM-G3** as a guide and mark the locations of the pilot holes with a marking pen. With a 5/64" drill bit, drill out the marked locations, drilling no more than 1/4" deep! Place the **VSM-G3** over the pilot holes and secure it to the dash using the two (3) provided #8 X 1/2" screws.
4. Once the **VSM-G3** is secured and flush to its mounting location, place the dash back together in the reverse manner in which it was disassembled. You have successfully installed your **VSM-G3**!



Note: See the Assembly Instructions for G3 Components for additional information.

Pro.Fit International, Inc.® may not be held liable for any damage to a vehicle before, during or after the installation or removal of this VSM-G3™.
Pro.Fit International may not be held liable for any personal injury resulting from accident or improper installation.
Pro.Fit International, Inc. Bloomington, MN 55420, Ph: 952-641-4700 or 800.388.0073 Fx: 952-641-4701

Installation Difficulty

● ● ○ ○ ○

Simple Advanced

**View Updated Instructions
Online at
www.pro-fit-intl.com**