



TOYOTA COROLLA (1993-1997)

PART NUMBER: **TY-52-97**

PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS Pro.Fit VSM®.

All instructions assume a drivers seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

Pro.Fit logo and part number will be right side up and readable when installed.

TOOLS REQUIRED: #1 Phillips screwdriver, hook tool, marking pen, 5/64" drill bit, drill.

PARTS INCLUDED: Pro.Fit VSM®, two(2) #8 x 3/8" screws, instructions.

LOCATION: To the right of the climate control.

STEP 1.

Begin by removing air conditioning switch button by gasping with your fingers and pulling. This will slide out. Remove four (4) knobs on climate control levers by using fingers to pull off. Set aside.

STEP 2.

Locate and remove two (2) Phillips screws under radio trim bezel. Insert hook tool at lower right corner of the radio trim bezel, between the bezel and the ash pad, pull back to release. These clips are tight, pull firmly. Repeat in top right section of bezel. Using your hands, continue pulling to release remaining two (2) clips on left side. disconnect wiring harnesses for defrosting unit, flashers, and/or clock. Set bezel aside.

STEP 3.

Locate and remove four (4) Phillips screws which hold the climate control unit in place. Slide climate control unit out until the **Pro.Fit VSM®** can slide behind the right side of climate control mounting bracket. Align **Pro.Fit VSM®** with the hole from the upper right hand screw of climate control mounting bracket. Slide climate control unit back into cavity and insert and tighten all four (4) factory screws.


STEP 4.

Using the two (2) holes remaining in **Pro.Fit VSM®** as a guide, drill pilot holes using the 5/64" drill bit and drill. Insert and tighten with provided screws. Install hang-up cup onto **Pro.Fit VSM®**. Reassemble dash.

This completes the installation of your **Pro.Fit VSM®**.



Pro.Fit International, Inc.® may not be held liable for any damage to a vehicle before, during or after the installation or removal of this Pro.Fit VSM®. Pro.Fit may not be held liable for any personal injury resulting from accident or improper installation. Pro.Fit International, Inc.® 1335 Eagandale Court, Eagan, MN 55121, Ph: 651-688-3588 or 800-388-0073 Fx: 651-688-9876



© Pro.Fit International, Eagan, MN 2004

